



# TECHUP

Tel:43-1-6150 499 Fax:43-1-61 50 499 - 89  
 Email:yue@techup.at Website: www.techup.at



## T8 Super bright SMD LED tube series

T8-8W - 60cm /2ft						
Product code : T8-6-8		TUV / ETL /CE / Rohs approval				
Dimension	mm	600 x 26	View Angle	Degree	120	
LED type	/	SMD3528	Color index	Ra	>75	
LED QTY	pcs	120	Power factor	PF	>90	
Input voltage	V	AC85V-265V	LED forward current	mA	18	
Housing material	Al + transparent cover		Operating frequency	Hz	50/60	
Luminous Flux	Warm W	750lm	Luminous Flux 5500k	1M	90-100lux	
	Pure W	850lm		2M	60-70lux	
	Cold w	850lm		3M	40-50Lux	
Luminous Efficiency	Lm/w	100	Environment Tempeture	°C	-20~+60	
Power	Watt	8	Equal conventional tube	Watt	25	
Life time	hrs	>50,000hrs	Certificate	CE / Rohs / TUV / ETL		
Color temperature	TC	WW: 3000-3500K,PW:4000-4500; 5500-6500K, CW:> 7000K				
Advantage of led tube	1) Aluminum heat sink + Aluminum PCB board for good heat dissipation 2) The end cap with screw to fix and own new patent					
Packing information	Carton Size :: 67 x 23 x 23cm, 25pcs/Carton , Actual Gross weight :6KG/carton ; CBM weight:7kg/carton					
T8-10W - 60cm /2ft						
Product code : T8-6-10		TUV / ETL /CE / Rohs approval				
Dimension	mm	600 x 26	View Angle	Degree	120	
LED type	/	SMD3528	Color index	Ra	>75	
LED QTY	pcs	144	Power factor	PF	>90	
Input voltage	V	AC85V-265V	LED forward current	mA	18	
Housing material	Al + transparent cover (Frosted/stripe available)		Operating frequency	Hz	50/60	
Luminous Flux	Warm W	850lm	Luminous Flux 5500k	1M	110-120Lux	
	Pure W	1000lm		2M	90-100Lux	
	Cold w	1000lm		3M	60-70Lux	
Luminous Efficiency	Lm/w	100	Environment Tempeture	°C	-20~+60	
Power	Watt	10	Equal conventional tube	Watt	25	
Life time	hrs	>50,000hrs	Certificate	CE / Rohs / TUV / ETL		
Color temperature	TC	WW: 3000-3500K,PW:4000-4500; 5500-6500K, CW:> 7000K				
Advantage of led tube	1) Aluminum heat sink + Aluminum PCB board for good heat dissipation 2) The end cap with screw to fix and own new patent					
Packing information	Carton Size :: 67 x 23 x 23cm, 25pcs/Carton , Actual Gross weight :6KG/carton ; CBM weight:7kg/carton					



# TECHUP

Tel:43-1-6150 499 Fax:43-1-61 50 499 - 89  
 Email:yue@techup.at Website: www.techup.at



## T8 Super bright SMD LED tube series

T8-15W - 120cm /4ft						
Product code : T8-12-15			TUV / ETL / CE / Rohs approval			
Dimension	mm	1200 x 26	View Angle	Degree	120	Picture 
LED type	/	SMD3528	Color index	Ra	>75	
LED QTY	pcs	240	Power factor	PF	>95	
Input voltage	V	AC85V-265V	LED forward current	mA	18	
Housing material	Al + transparent cover		Operating frequency	Hz	50/60	
Luminous Flux	Warm W	1450lm	Luminous Flux 5500k	1M	170-180lux	
	Pure W	1600lm		2M	120-130lux	
	Cold w	1600lm		3M	70-80lux	
Luminous Efficiency	Lm/w	100	Environment Temperture	°C	-20~+60	
Power	Watt	15	Equal conventional tube	Watt	40	
Life time	hrs	>50,000hrs	Certificate	CE / Rohs / TUV / ETL		
Color temperature	TC	WW: 3000-3500K,PW:4000-4500; 5500-6500K, CW:> 7000K				
Advantage of led tube	1) Aluminum heat sink + Aluminum PCB board for good heat dissipation 2) The end cap with screw to fix and own new patent					
Packing information	Carton Size :: 127 x 23 x 23cm, 25pcs/Carton , Actual Gross weight:11.5KG/carton; CBM weight:13.5kg/Carton					
T8-18W - 120cm /4ft						
Product code : T8-12-20			TUV / ETL / CE / Rohs approval			
Dimension	mm	1200 x 26	View Angle	Degree	120	Picture 
LED type	/	SMD3528	Color index	Ra	>75	
LED QTY	pcs	288	Power factor	PF	>95	
Input voltage	V	AC85V-265V	LED forward current	mA	18	
Housing material	Al + transparent cover (Frosted/stripe available)		Operating frequency	Hz	50/60	
Luminous Flux	Warm W	1850lm	Luminous Flux 5500k	1M	180-190lux	
	Pure W	2000lm		2M	130-140lux	
	Cold w	2000lm		3M	80-90lux	
Luminous Efficiency	Lm/w	100	Environment Temperture	°C	-20~+60	
Power	Watt	20	Equal conventional tube	Watt	45	
Life time	hrs	>50,000hrs	Certificate	CE / Rohs / TUV / ETL		
Color temperature	TC	WW: 3000-3500K,PW:4000-4500; 5500-6500K, CW:> 7000K				
Advantage of led tube	1) Aluminum heat sink + Aluminum PCB board for good heat dissipation 2) The end cap with screw to fix and own new patent					
Packing information	Carton Size :127x 23 x 23cm, 25pcs/Carton , Actual Gross weight:12KG/carton; CBM Weight:13.5kg/Carton					

# TECHUP

Tel:43-1-6150 499 Fax:43-1-61 50 499 - 89  
 Email:yue@techup.at Website: www.techup.at



## T8 Super bright SMD LED tube series

T8-20W - 150cm /5ft						
Product code : T8-15-20			TUV / ETL / CE / Rohs approval			
Dimension	mm	1500 x 26	View Angle	Degree	120	Picture 
LED type	/	SMD3528	Color index	Ra	>75	
LED QTY	pcs	300	Power factor	PF	>95	
Input voltage	V	AC85V-265V	LED forward current	mA	18	
Housing material	Al + transparent cover		Operating frequency	Hz	50/60	
Luminous Flux	Warm W	1850lm	Luminous Flux 5500k	1M	190-200Lux	
	Pure W	2000lm		2M	140-150lux	
	Cold w	2000lm		3M	100-110lux	
Luminous Efficiency	Lm/w	100	Environment Tempeture	°C	-20~+60	
Power	Watt	20	Equal conventional tube	Watt	50	
Life time	hrs	>50,000hrs	Certificate	CE / Rohs / TUV / ETL		
Color temperature	TC	WW: 3000-3500K,PW:4000-4500; 5500-6500K, CW:> 7000K				
Advantage of led tube	1) Aluminum heat sink + Aluminum PCB board for good heat dissipation 2) The end cap with screw to fix and own new patent					
Packing information	Carton Size :: 157 x 23 x 23cm, 25pcs/Carton , Actual Gross weight:15KG/carton;CBM Weight:17kg/Carton					
T8-22W - 150cm /5ft						
Product code : T8-15-22			TUV / ETL / CE / Rohs approval			
Dimension	mm	1500 x 26	View Angle	Degree	120	Picture 
LED type	/	SMD3528	Color index	Ra	>75	
LED QTY	pcs	396	Power factor	PF	>90	
Input voltage	V	AC85V-265V	LED forward current	mA	18	
Housing material	Al + transparent cover (Frosted/stripe available)		Operating frequency	Hz	50/60	
Luminous Flux	Warm W	2350lm	Luminous Flux @5500k	1M	270-280lux	
	Pure W	2500lm		2M	170-180lux	
	Cold w	2500lm		3M	130-140lux	
Luminous Efficiency	Lm/w	115	Environment Tempeture	°C	-20~+60	
Power	Watt	22	Equal conventional tube	Watt	58	
Life time	hrs	>50,000hrs	Certificate	CE / Rohs / TUV / ETL		
Color temperature	TC	WW: 3000-3500K,PW:4000-4500; 5500-6500K, CW:> 7000K				
Advantage of led tube	1) Aluminum heat sink + Aluminum PCB board for good heat dissipation 2) The end cap with screw to fix and own new patent					
Packing information	Carton Size :: 157 x 23 x 23cm, 25pcs/Carton , Actual Gross weight:15.5KG/carton;CBM Weight:17kg/Carton					