

## Hochwertig zoombare LED Strahler

Model No.	Power	Control method	Input Voltage	LED brand	Beam angle	Adapter	Lumen ( $\pm 200\text{lm}$ )	CRI	Dimension (mm)
TPS110W	10W	Tridonic non-Dim	AC220V-240V	Citizen	10°-50°	4 wire	820	>90 (97 Option)	D60 * H120
TPS112WD	12W	Dali integrated (TCI)	AC220V-240V	Citizen	10°-50°	6 wire	900	>90 (97 Option)	D60 * H120
TPA120W	20W	Tridonic non-Dim	AC220V-240V	Citizen	12°-60°	4 wire	1900	>90 (97 Option)	D90 * H188
TPA125W	25W	Tridonic non-Dim	AC220V-240V	Citizen	12°-60°	4 wire	2200	>90 (97 Option)	D90 * H188
TPA130W	30W	Tridonic non-Dim	AC220V-240V	Citizen	12°-60°	4 wire	2500	>90 (97 Option)	D90 * H188
TPA130WD	30W	Dali integrated (TCI)	AC220V-240V	Citizen	12°-60°	6 wire	2500	>90 (97 Option)	D90 * H188

CCT : 2700K/3000K/4000K



TPS110W



TPS112WD



TPA120W/TPA125W/TPA130W



TPA130WD




20W,25W,30W Non-Dim Treiber  
wechselbar

Zubehör:



Spezielle Lens cover:



Oval Lens cover



Softening Lens cover



Flood wide Lens cover (Wall washer)

Alle Leuchten sind geeignet für 3 Phasen Schienen.

Alle Dali Dimmer für 6 Kabel, Einstellung nur Helligkeit.

Technische Änderungen und Anpassungen vorbehalten.

Auf Modelle mit Tridonic Treiber 5 Jahre Garantie.

Auf Modelle mit anderen Treiber 3 Jahre Garantie.